



17"

SXGA

170B7CG



## Extremely convenient display for business users

- With SmartManage LAN-based remote monitor management, Philips Perfect Panel™ warranty and a full range of convenient features, the I70B7 delivers great and convenient display at a very attractive total cost of ownership.

## Best total cost of ownership solution

- Empowered for Windows Vista
- SmartManage compatibility enables LAN-based asset management
- Power consumption below the industry average

## Outstanding front of screen performance

- ISO 13406-2 Class I compliant dot-defect-free display
- 5ms fast response time
- SXGA 1280 x 1024 resolution for sharper display
- Dual input accepts both analog VGA and digital DVI signals

## Maximum comfort for maximum productivity

- Tilt, swivel and height-adjust for an ideal viewing position

## Great convenience

- USB port for convenient peripheral connections
- Easy to adjust display settings with Philips SmartControl
- Built-in speakers for audio without desktop clutter

**PHILIPS**  
sense and simplicity

## Specifications

### Picture/Display

- **LCD panel type:** 1280 x 1024 pixels, Anti-glare polariser, RGB vertical stripe
- **Panel size:** 17" / 43 cm
- **Effective viewing area:** 337.9 x 270.3 mm
- **Pixel pitch:** 0.264 x 0.264 mm
- **Brightness:** 300 cd/m<sup>2</sup>
- **Contrast ratio (typical):** 800:1
- **Display colours:** 16.7 M
- **Viewing angle:** 176° (H) / 170° (V), @ C/R > 5
- **Response time (typical):** 5 ms
- **White Chromaticity, 6500K:** x = 0.313 / y = 0.329
- **White Chromaticity, 9300K:** x = 0.283 / y = 0.297
- **Maximum Resolution:** 1280 x 1024 @ 75 Hz (digital input)
- **Recommended Resolution:** 1280 x 1024 @ 60 Hz (digital input)
- **Video Dot Rate:** 140 MHz
- **Horizontal Scanning Frequency:** 30 - 83 kHz
- **Vertical Scanning Frequency:** 56 - 76 Hz
- sRGB

### Connectivity

- **Signal Input:** Analog (VGA), DVI-D, PC Audio in
- **Audio output:** Stereo Audio (3.5 mm jack) 1x
- **USB:** 1 x USB 2.0
- **Video Sync Input Signal:** Composite Sync, Separate Sync, Sync on Green
- **Video input impedance:** 75 ohm
- **Sync input impedance:** 2.2k ohm
- **Video input signal levels:** 0.7 Vpp

### Convenience

- **Built-in Audio:** 2 W RMS x 2 Stereo Speakers
- **Convenience Enhancements:** On-screen Display, SmartManage enabled
- **Monitor Controls:** Auto, Brightness Control (Up/Down), Left/Right, Menu (OK), Power On/Off, Volume control
- **OSD Languages:** English, French, German, Italian, Russian, Spanish
- **Other convenience:** Kensington lock compatible, FlexiHolder
- **Plug & Play Compatibility:** DDC/CI, sRGB, Windows 98/ME/2000/XP/Vista

- **Regulatory Approvals:** CE Mark, EMC, Energy Star, FCC-B, UL, CSA, SEMKO, TCO '03, TÜV GS, TÜV Ergo
- **Swivel:** +/- 60°
- **Tilt:** -5° to 25°
- **VESA Mount:** 100 x 100 mm

### Accessories

- **Included Accessories:** AC Power Cord, Audio Cable, USB cable, VGA cable
- **Optional accessories:** Super Ergo Base
- User Manual

### Dimensions

- **Box dimensions (W x H x D):** 449 x 182 x 452 mm
- **Box dimensions in inch (W x H x D):** 17.7 x 7.2 x 17.8 inch
- **Set dimensions (W x H x D):** 382.5 x 342.8 x 61.5 mm
- **Set dimensions in inch (W x H x D):** 15.1 x 13.5 x 2.4 inch
- **Set dimensions with stand (W x H x D):** 382.5 x 387.2 x 198.7 mm
- **Set dimensions with stand in inch (W x H x D):** 15.1 x 15.2 x 7.8 inch
- **Height adjustment range:** 60 mm
- **Height adjustment range (inch):** 2.4 inch
- **MTBF:** 50,000 hrs
- **Relative Humidity:** 20% - 80%
- **Temperature range (operation):** 5°C to 40°C
- **Temperature range (storage):** -20°C to 60°C
- **Product weight (+stand):** 5.2 kg
- **Product weight (+stand) (lb):** 11.5 lb
- **Weight incl. Packaging:** 6.5 kg
- **Weight incl. Packaging (lb):** 14.3 lb

### Power

- **Complies with:** Energy Star
- **Consumption:** 33W (Typical)
- **Off Mode:** < 1 W
- **Power LED indicator:** Operation - green, Stand by/sleep - Amber
- **Power supply:** Built-in, 100-240VAC, 50/60Hz

## Product highlights

### Windows Vista ready

Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organising information for work or play quick, efficient and easy.

### SmartManage enabled

SmartManage is a system for monitoring, managing and checking status of display devices as well as delivering remote support to users who experience difficulties - all accomplished over a LAN.

### Lower power consumption

Reduction of the electrical power required to operate a device.

### PerfectPanel™

Bright dots and dark dots are defects in a LCD panel. While some manufacturers still consider bright and dark defects in a LCD panel an inevitable part of the manufacturing process, Philips doesn't. Philips monitors, compliant with ISO 13406-2 Class I standard, are produced with zero tolerance for LCD panel defects and backed by Philips PerfectPanel™ globally valid warranty providing repair or replacement of any LCD monitors that display even a single defective bright or dark dot.

### 5ms on/off response time

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

### Dual input

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

### Compact Ergo Base

The Compact Ergo Base is a 'people friendly' Philips monitor base that tilts, swivels and height adjusts so each user can position the monitor for maximum viewing comfort and efficiency.

### USB 2.0 port

The universal serial bus or USB is a standard protocol for linking PCs and peripherals. Because it delivers high speed at a low cost, USB has become the most popular method for connecting peripheral devices to a computer. A port located on a monitor directly in the user's line of sight provides easy, high-speed connectivity for USB devices at a convenient location. (USB 2.0 support is dependent on your PC's USB configuration; when connected to a PC that supports USB 2.0, your monitor is USB 2.0 compatible)

### SmartControl

PC software for fine tuning display performance and settings. Philips offers users two choices for display setting adjustment. Either navigate the multilevel On Screen Display menu through buttons on the display itself or use the Philips SmartControl software to easily adjust the various display settings in a familiar way.

### Built-in speakers

Audio speakers built into a display device.



Issue date 2008-08-18

Version: 8.0.14

12 NC: 8639 000 16887  
EAN: 87 10895 95625 3

© 2008 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)